
THE HYBRID" TRIM/KIEF BAG SETUP

TRIMINATOR

KNOW YOUR BAGS



WET TRIMMING


The trim bag should be installed to collect and contain discarded plant material.


1

Swing both bag holder arms perpendicular to the machine until they lock into place.

2

Slide the loops on the trim bag over the tabs on the arms.





 \times

3

Position the circular mouth of the trim bag over the outlet of the fan housing, and cinch the drawstring around the raised lip to secure the bag to the machine.

4

Ensure the trim bag is zipped



completely closed.

DRY TRIMMING


Dry trimming can result in kief dust in the exhaust air stream. The normal trim bag will not capture the kief dust, but the kief bag will. Prior to dry trimming, both the trim and kief bags should be installed to contain discarded plant material and dust.


1

Swing both bag holder arms perpendicular to the machine until they lock into place.

2

Slide the arms through the slits in the kief bag and put the mouth over the fan outlet.





3

Unzip the kief bag and put the trim bag inside. Slide the trim bag loops over the arms.

4

Slide the trim bag mouth over the fan outlet and tighten the drawstring.

5


Slide the elastic kief bag mouth over the drawstring and onto the fan exhaust.

6

Ensure the trim and kief bags are both zipped completely closed.

EMPTYING TRIM BAG

- Power down the machine
- Unzip the kief bag (DO NOT remove it from the arms)
- Loosen drawstring on the trim bag
- Slide trim bag loops off of the arms
- Unzip and empty the trim into a tote





- 1 Soak the trim and kief bags in a mixture of warm water and degreaser such as GMP Solutions Step 1 Cleaner for 10-15 minutes.
- 2 Gently agitate to remove debris.
- **3** Rinse thoroughly and hang dry.

QUESTIONS?

CONTACT A TRIMINATOR EXPERT 1-530-265-4277 INFO@THETRIMINATOR.COM THETRIMINATOR.COM



